

Pole Display

2-Line Alpha-Numeric Pole Display



Improve Security and Customer Confidence

Build a strong relationship with your customer by clearly displaying each item as it is registered into your electronic cash register or point of sale system. Customers can easily monitor the transaction as it is entered, clearly viewing the price of each item. The SAM4s display provides two lines, so that both the price and the description of the item are displayed simultaneously. With each transaction closely monitored by the customer, the opportunity for employee theft and fraud is limited. The SAM4s display is connected by a standard serial interface and is compatible with most systems.

- Vacuum Fluorescent Display 2 Lines of 20 Columns
- Adjustable Display Panel For Best Viewing Angle
- Adjustable Height and Rotation
- Supports All Popular Emulations
- Serial Cable Included



Up to Five Pole Display Heights Available by Mixing and Matching the Long and Short Extension Poles:
 5-1/8" 9-1/16" 13" 15-3/4" 19-5/8"

Features

- Vacuum Fluorescent Display 2 Lines of 20 Columns
- Adjustable Display Panel For Best Viewing Angle
- Adjustable Height and Rotation
- RS-232C Interface, 4,800 to 38,400 Baud Rate
- Self-Test Function
- User-Defined and International Character Set Standard
- Supports All Popular Emulations
- Carton Includes Display Module, Base, One Long Extension Pole, Two Short Extension Poles, Four Rubber Pads, Power Adapter, Serial Cable (DB-9F – DB-9M) and User's Manual

Specifications

Customer Display:	Vacuum Fluorescent Display
VFD Color:	Green
Display Format:	40 Characters (20 Columns x 2 Lines)
Character Type:	16 Sets of International Characters / 224 User Definable Characters
Character Font:	5 x 7 Dot Matrix
Character Size:	9.15mm H x 5.45mm W
Character Pitch:	8.45mm
Interface:	One RS-232C
Data Transmission:	Serial, Asynchronous
Baud Rate:	4800 / 9600 / 19200 / 38400
Data Bits:	8 Bits
Parity:	None
Stop Bits:	1
Connector Type:	D-Sub 9P / RJ45
USB:	Two USB 2.0
Emulations:	CD5220 / DSP800 / EPSON ESC / POS / ADM787 / ADM788 / EADDEX / UTC-S / UTC-E / ICD-2002
Power Supply Voltage:	DC 7 ~ 12 Volts
Power Consumption:	4.5 Watts (Maximum)
Tilt Angle:	0 ~ 40°
Swivel Angle:	350°
Dimensions –	Panel: 9-1/4" W x 1-1/2" D x 3-1/4" H
	Total Height: 5-1/8" ~ 19-5/8"
	Base: 8-1/8" W x 5-1/4" D x 1" H
Shipping Weight:	4 lbs.

All product and company names are trademarks or registered trademarks of their respective owners.